

The **simalube IMPULSE connect** is the latest generation of the pressure booster from the simalube family. The proven functions of the IMPULSE have been supplemented with the option of connecting the device to a smartphone via **Bluetooth®**. In connection with the newly developed **«simatec world of maintenance» app,** the devices can be easily configured and then monitored without having to be directly at the lubrication point. Information such as general status, fill level, lubricant, size, start and change date etc. is displayed to the user and easy to read in the app.

Your advantages:

- Communication via Bluetooth®
- Configuration and monitoring with the «simatec world of maintenance» app
- Universally configurable
- Reusable
- 10 bar pressure














Your benefits with simalube IMPULSE connect

- Cost savings through faster, easier and safer inspection rounds
- Easier monitoring, clear and comprehensive display of the current operating status
- Management of Iubrication points in Lubechart
- Digital support through the app: user guidance in the form of animated installation and operating instructions
- Less wear and tear on the components thanks to continuous lubrication; in time mode, temperature-independent
- No production interruptions for maintenance and monitoring purposes, this results in a higher availability of the production systems
- Temperature-independent grease supply to the lubrication points thanks to the option of operating the IMPULSE connect in «time-controlled» mode

simatec app «simatec world of maintenance»

With the «simatec world of maintenance» app, simatec ag has created a platform for easier and more efficient management of lubrication work. The app offers the user the possibility to record lubrication points, to set the necessary parameters for the lubrication and to control or monitor all activities around the lubrication. The simulube IMPULSE connect equipped with Bluetooth® can be configured directly via the app, the current operating status can be viewed from a distance of up to 20 m via the app.



Technical data

simalube IMPULSE connect	Automatic pressure booster for the simalube lubricator
Drive system	Electromechanical
Power supply	Battery pack* 6 V 2.3 Ah (Alkaline)
Function display	LED status display – green/red/blue every 10 seconds. Monitoring of the operating status via the «simatec world of maintenance» app.
Connectivity	MPULSE connect supports Bluetooth® Low Energy 5.0 standard. The connection can reach up to 20 m in an interference free open field environment.
Working pressure	up to 10 bar
Operating temperature	−10 °C to +55 °C (14 °F to 131 °F)
Lubricator volume	60 ml, 125 ml, 250 ml
Lubricant	Greases up to NLGI 2 or oils
Warranty & period of use	3 years from the production date or until 10 simalube lubricators (125 ml) have been emptied

Download the new simatec app:







